

Specs

● Package contents

- Speakerphone
- Camera
- Remote control
- 10m speakerphone cable (RJ45)
- 5m USB cable (USB2.0 mini B connect to PC)
- 0.9m 3.5mm aux cable
- Power supply
- Quick-start guide
- Tabletop/wall/ceiling mount
- Velcro
- USB clip

● Camera

- Zoom: 18X total zoom (**12X optical zoom**)
- Minimum working distance: 1.5 meter
- Pan step 0.45°; tilt step 0.25° (precisely controlled by remote control)
- f/1.8 to f/2.8 (fast lens, perfect picture even in low light)
- Full HD 1080p
- ±130° pan; +90°/-25° tilt
- **82° FOV (diagonal)**
- Multi-element, multi-coating auto-focus optics
- Advanced settings in download app
- Standard tripod thread
- Flip horizontal/vertical, capable for reverse ceiling mount
- Kensington security slot

● Speakerphone

- Full duplex microphone array up to 2 daisy-chain speakerphone
- 3.5mm Line-in (aux) cable connects to BYOD smartphones or PC as speakerphone
- Touch controls for volume down, up, mute, phone input
- Microphones, 3 directional microphones supporting 360° pick up in 9m diameter range
- 10W speaker, max output 95dB SPL
- Echo cancellation
- Noise suppression

● Remote control

- 10 camera presets

● System requirements*

- Windows® 7/ 8/8.1/10
- Mac OS® X 10.7 or higher
- Google Chromebook version 29.0.1547.70, Platform 4319.79.0

● Hardware requirements*

- 2.4 GHz Intel® Core 2 Duo processor
- 2 GB RAM or more
- USB 2.0 port

● Power supply

- AC 100V ~ 220V
- Consumption: DC12/4A

● Physical characteristics

- Camera: 180 x 144 x 184mm / 1.5kg
- Speakerphone: 210 x 209 x 59mm / 1.0kg
- Remote control: 200 x 50 x 20mm / 0.091kg

● **Compliance and tools**

- YUV, MJPEG, H.264
- USB 2.0 compatible
- VISCA via RS232*
- UVC compatible video and audio for broad application compatibility
- Downloadable diagnostic tool, field firmware upgrade tool, app for advanced features and settings

*Please check AVer product web page for compatible VISCA commands and devices.